

Supplier	TOSHIBA
Unutarnja jedinica	RAS-B10N4KVRG-E
Vanjska jedinica	RAS-10J2AVSG-E1

Sound power level

Unutarnja jedinica (hlađenje)	dB	54
Vanjska jedinica (hlađenje)	dB	57
Unutarnja jedinica (grijanje)	dB	54
Vanjska jedinica (grijanje)	dB	59

Radni medij

Tip		R32
Potencijal globalnog zatopljenja	kgCO ₂ eq	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class		A+++
Design load (P _{designc})	kW	2.5
Seasonal efficiency (SEER)		8.60
Sezonska snaga električnog priključka (Q _{CE}) (*)	kWh/annum	102

(*) Na temelju standardnih rezultata mjerenja. Stvarana godišnja potrošnja ovisi o načinu uporabe i lokaciji sustava.

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+++	A+++	x
Design load (Pdesignh)	kW	2.5	3.4	x,x
Seasonal efficiency (SCOP)		5.10	6.70	x,xx
Sezonska snaga električnog priključka (Q _{HE}) (*)	kWh/annum	684	706	x
Pričuvni kapacitet grijanja	kW	0.00		
Navedeni kapacitet grijanja pri sobnoj temperaturi od 20° C i vanjskoj temperaturi zraka (Tj)				
Tj= -7°C (Pdh)	kW	2.21	-	x,xx
Tj= 2°C (Pdh)	kW	1.35	1.35	x,xx
Tj= 7°C (Pdh)	kW	0.87	0.87	x,xx
Tj= 12°C (Pdh)	kW	0.91	0.91	x,xx
Tj=bivalent temperature (Pdh)	kW	2.21	3.40	x,xx
Tjgranična radna temperatura (Pdh)	kW	3.10	3.10	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx

(*) Na temelju standardnih rezultata mjerenja. Stvarana godišnja potrošnja ovisi o načinu uporabe i lokaciji sustava.