

INVERTERSKI MULTI SUSTAVI: Vanjske jedinice



RAS-2M14U2AVG-E
RAS-2M18U2AVG-E
RAS-3M18U2AVG-E



RAS-3M26U2AVG-E
RAS-4M27U2AVG-E
RAS-5M34U2AVG-E

VANJSKA JEDINICA			MULTISPLIT ZA 2 PROSTORIJE		MULTISPLIT ZA 3 PROSTORIJE		MULTISPLIT ZA 4 PROSTORIJE	MULTISPLIT ZA 5 PROSTORIJA
			RAS-2M14U2AVG-E	RAS-2M18U2AVG-E	RAS-3M18U2AVG-E	RAS-3M26U2AVG-E	RAS-4M27U2AVG-E	RAS-5M34U2AVG-E
Učin hlađenja	kW	❄️	4,00	5,20	5,20	7,50	8,00	10,00
Raspon učina hlađenja (min. – maks.)	kW	❄️	1,60 - 4,90	1,70 - 6,20	2,40 - 6,50	4,10 - 9,00	4,20 - 9,30	3,70 - 11,00
Potrošnja energije (min./nom./maks.)	kW	❄️	0,92	1,34	1,17	2,00	2,29	2,98
Koeficijent energetske učinkovitosti EER	W/W	❄️	4,35	3,88	4,44	3,75	3,50	3,36
Sezonski koeficijent energetske učinkovitosti SEER		❄️	6,73	6,90	6,80	6,19	6,11	6,31
Razred energetske učinkovitosti		❄️	A++	A++	A++	A++	A++	A++
Radno područje za vanjsku temperaturu (min. – maks.)	°C	❄️	-10/+46	-10/+46	-10/+46	-10/+46	-10/+46	-10/+46
Učin grijanja	kW	🔥	4,40	5,60	6,80	9,00	9,00	12,00
Radno područje za vanjsku temperaturu (min. – maks.)	°C	🔥	-20/+24	-20/+24	-20/+24	-15/+24	-15/+24	-15/+24
Potrošnja energije (min./nom./maks.)	kW	🔥	0,89	1,19	1,58	2,20	1,93	2,83
Koeficijent energetske učinkovitosti COP	W/W	🔥	4,94	4,71	4,30	4,09	4,67	4,24
Sezonski koeficijent energetske učinkovitosti SCOP		🔥	4,60	4,60	4,60	4,44	4,26	4,08
Razred energetske učinkovitosti		🔥	A++	A++	A++	A++	A++	A+
Raspon učina grijanja (min.-maks.)	kW	🔥	1,30 - 5,20	1,30 - 7,50	1,90 - 8,00	2,00 - 11,20	2,90 - 11,70	2,70 - 14,00
Strujno napajanje	V/Ph+N/Hz		220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50
Preporučeni osigurač	A		13	13	13	16	20	20
Razina zvučnog tlaka (niska/srednja/visoka)	dB(A)	❄️	45	47	47	48	48	52
Razina zvučnog tlaka (niska/srednja/visoka)	dB(A)	🔥	46	50	50	49	49	55
Duljina cjevovoda, (maks.)	m		30	30	50	70	70	80
Duljina cjevovoda/unutarnja jedinica (min.)	m		2	2	2	3	3	3
Duljina cjevovoda/unutarnja jedinica (maks.)	m		20	20	25	25	25	25
Visinska razlika (maks.)	m		10	10	10	15	15	15
Tip kompresora			Twin-Rotary	Twin-Rotary	Twin-Rotary	Twin-Rotary	Twin-Rotary	Twin-Rotary
Radna tvar			R32	R32	R32	R32	R32	R32
Količina punjenja radne tvari	kg		1,02	1,02	1,05	1,92	1,92	2,39
Dimenzije (VxŠxD)	mm		630 x 800 x 300	630 x 800 x 300	630 x 800 x 300	890 x 900 x 320	890 x 900 x 320	890 x 900 x 320
Težina	kg		43	45	46	72	72	78
Cijena	kn		8.418,-	8.834,-	12.015,-	13.752,-	15.881,-	18.353,-

Tablica s kombinacijama ZA INVERTERSKE MULTI SUSTAVE

VANJSKA JEDINICA	RAS-2M14U2AVG-E	RAS-2M18U2AVG-E	RAS-3M18U2AVG-E	RAS-3M26U2AVG-E			
1 uređaj*	07 10 13	07 10 13 16	07 10 13 16	07 10 13 16 18 22 24			
2 uređaja	10+07 10+10 13+07 13+10 13+13	07+07 10+07 10+10 13+07 13+10 13+13 16+07 16+10 16+13 16+16	07+07 10+07 10+10 13+07 13+10 13+13 16+07 16+10 16+13 16+16	07+07 10+07 10+10 13+07 13+10 13+13 16+07 16+10 16+13 16+16 18+07 18+10 18+13 18+16 18+18 22+07 22+10 22+13 22+16 22+18 24+07 24+10 24+13 24+16 24+18			
3 uređaja			07+07+07 10+07+07 10+10+07 10+10+10 13+07+07 13+10+07 13+10+10 13+13+07 13+13+10 13+13+13 16+07+07 16+10+07 16+13+07	07+07+07 10+07+07 10+10+07 10+10+10 13+07+07 13+10+07 13+10+10 13+13+07 13+13+10 13+13+13 16+07+07 16+10+07 16+10+10	16+13+07 16+13+10 16+16+07 16+16+10 16+16+13 16+16+16 18+07+07 18+10+07 18+10+10 18+13+07 18+13+10 18+13+13	18+16+07 18+16+10 18+16+13 18+16+16 22+07+07 22+10+07 22+10+10 22+13+07 22+13+10 22+13+13 22+16+07 22+16+10 22+16+13	22+16+16 24+07+07 24+10+07 24+10+10 24+13+07 24+13+10 24+13+13 24+16+07 24+16+10 24+16+13
4 uređaja							
5 uređaja							

* 1 uređaj samo za režim hlađenja

