

Supplier	TOSHIBA
Unutarnja jedinica	RAS-B10J2KVSG-E
Vanjska jedinica	RAS-10J2AVSG-E

## Sound power level

Unutarnja jedinica (hlađenje)	dB	53
Vanjska jedinica (hlađenje)	dB	57
Unutarnja jedinica (grijanje)	dB	53
Vanjska jedinica (grijanje)	dB	59

## Radni medij

Tip		R32
Potencijal globalnog zatopljenja	kgCO <sub>2</sub> eq	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

## Cooling

Energy efficiency class		A+++
Design load (P <sub>designc</sub> )	kW	2.5
Seasonal efficiency (SEER)		8.60
Sezonska snaga električnog priključka (Q <sub>CE</sub> ) (*)	kWh/annum	102

(\*) Na temelju standardnih rezultata mjerenja. Stvarana godišnja potrošnja ovisi o načinu uporabe i lokaciji sustava.

## Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+++	A+++	x
Design load (Pdesignh)	kW	2.5	1.3	x,x
Seasonal efficiency (SCOP)		5.10	6.60	x,xx
Sezonska snaga električnog priključka (Q <sub>HE</sub> ) (*)	kWh/annum	686	284	x
Pričuvni kapacitet grijanja	kW	0.52		
<b>Navedeni kapacitet grijanja pri sobnoj temperaturi od 20° C i vanjskoj temperaturi zraka (Tj)</b>				
Tj= -7°C (Pdh)	kW	2.21	-	x,xx
Tj= 2°C (Pdh)	kW	1.35	1.35	x,xx
Tj= 7°C (Pdh)	kW	0.87	0.87	x,xx
Tj= 12°C (Pdh)	kW	0.97	0.97	x,xx
Tj=bivalent temperature (Pdh)	kW	2.21	1.35	x,xx
Tjgranična radna temperatura (Pdh)	kW	1.60	1.60	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx

(\*) Na temelju standardnih rezultata mjerenja. Stvarana godišnja potrošnja ovisi o načinu uporabe i lokaciji sustava.